



# 508H Chopped Strands

For PP, PE

508H Chopped Strands for Thermoplastics are coated with a silane-based sizing, compatible with PP and PE resins. 508H is designed for extrusion and injection molding processes, and is widely used in automotive, home appliance, transportation, and packing applications.



### Product Features

- ◎ Excellent strand integrity, low static, low fuzz, and good flowability
- ◎ Excellent detergent resistance
- ◎ Excellent mechanical properties and good color

### Identification

Example	ECS13-4.5-508H
Type of Glass	E
Chopped Strands	CS
Filament Diameter, $\mu\text{m}$	13
Chop Length, mm	4.5
Size Code	508H

### Technical Parameters

Filament Diameter (%)	Moisture Content (%)	Size Content (%)	Chop length (mm)
ISO 1888	ISO 3344	ISO 1887	Q/JS J0361
$\pm 10$	$\leq 0.10$	$0.60 \pm 0.15$	$\pm 1.0$

### Packaging

\* The product can be packed in bulk bags, heavy-duty box, and composite plastic woven bags;  
For example:  
Bulk bags can hold 900kg-1000kg each;  
Composite plastic woven bags can hold 15kg-25kg each.

#### Bulk bag

Length mm (in)	1030 (40.55)
Width mm (in)	1030 (40.55)
Height mm (in)	1000 (39.4)

#### Composite plastic woven bag

Length mm (in)	850 (33.46)
Width mm (in)	500 (19.68)
Height mm (in)	120 (4.72)

### Storage

Unless otherwise specified, fiberglass products should be stored in a dry, cool and rain-proof area. It is recommended that the room temperature and humidity should be always maintained at  $15^{\circ}\text{C} \sim 35^{\circ}\text{C}$  and 35%~65% respectively.



## JUSHI GROUP CO., LTD.

2010.04 版权所有：© 巨石集团有限公司 ® 巨石集团有限公司注册商标

Add: Tongxiang Economic Development Zone, Zhejiang 314500, PRC International Sales: +86-573-88181026 Fax: +86-573-88181058  
Domestic Sales: +86-573-88181016 Fax: +86-573-88136222 Customer Service: +86-573-88181017 Fax: +86-573-88181388  
Http://www.jushi.com E-mail: info@jushi.com